

# TOUCH-UP PAINT KIT INSTRUCTIONS

 Please follow the instructions for correct use

This product is a transitional product. It prevents the primer from corroding and rusting, and covers up scratches. If you want to restore it to its original state, it is recommended to return it to the factory for sheet



Touch up paint



Quick drying putty



Sandpaper



Putty scraper

## ABOUT COLOR DIFFERENCE

### Color difference problem

- **Factory VS Real-World Paint**  
Our paints are the same color as your vehicle's original factory paint. However, cars will naturally fade due to factors such as time, sunlight and weather, so there will be differences.
- **Spraying method**  
Hand-applied car paint will not be very smooth, so it will be darker.

### Check if the colors match

- **Test comparison**  
Please apply a paint color sample to the blank area and compare it to the paint on the hood or door.
- **Attention**  
If you feel that the paint does not match the car, please do not use it and return it. If you have already used it, you can clean it with alcohol solution within 5 minutes.



## TIPS ON USING PAINT

### Tips 1: Paint application method

- ! Avoid overlapping onto undamaged paint.
- ! Apply in one direction only (left to right) to match paint flow.
- ! DO NOT overbrush – this breaks pigment bonds and dulls gloss.

### Tips 2: Multi-layer repair

Damage Depth	Solution
Shallow scratches	2-3 thin coats 20 mins between layers
Deep metal exposure	① Filler paste → ② Sand → ③ 4+ coats

### Tip 4: After-repair care

- Wait 72 hours before washing/waxing/polishing to prevent peeling.
- Non-mirror finish is normal – use polishing compound during next car wash to blend colors.

### Tip 5: Modify Color

- Unsatisfied? Use alcohol patch or wet towel to wipe off wet paint within 5 minutes
- Color matching: Always test and repair under natural daylight (cloudy days alter perception).



## 1. Contrasting colors

Apply paint to the blank area of the manual and compare it with the car body color. After confirming that the color is consistent, proceed to the next step. If there is any difference, please contact customer service.



## 2. Clean the scratch

If the scratch is just a stain, just clean it and let it air dry. If there are burrs or rust on the scratch, you need to use sandpaper to gently polish it and then clean it. (Please do not polish too much to damage the original paint surface)



### 3. Filling the damage

Use filler compound and damage  
If your car paint damage is very shallow, you can skip this step, or if you are a novice, you can skip this step



### 4. Stirring paint

Shake the touch-up bottle vigorously up and down for 15 seconds. Shake it thoroughly and you can hear the sound of steel balls hitting each other inside.



**Tips**  
**Shake before use**



### 5. Apply paint

Surface scratches: Apply thinly 2-3 times from left to right, 20 minutes apart  
Deep scratches: After filling with putty, apply thinly 2-3 times from left to right, 20 minutes apart



### 6. Check the effect

Check the application effect. If the blemishes cannot be covered, repeat the application.



### 7. Repair Completed

Repair Completed.  
After 72 hrs, use polishing cloth for smooth texture.